
## **CASE STUDY |** Sealant And Adhesives Manufacturer







	FLOW	RATE 20,00	00 GALLONS PER DAY
		Surcharge Limit	Average Value Prior to MacDermid Envio's Treatment
	BOD	200mg/l	<b>2,000</b> mg / I
CHALLENGES	TSS	1,000mg/I	<b>30,000</b> mg / I
CHALLENGES			

Taking bigger steps to leave a smaller footprint

This popular sealant and adhesives manufacturer experienced multiple challenges resulting from creating emulsions:

- 1. Clogged water lines that can be expensive and time-consuming to fix
- **2.** Was not adequate enough to meet the 30,000 gallons of rinse water required for daily manufacturing operations
- 3. A failed investment in their own pretreatment solution

## **SOLUTION**

The facility had trouble getting their effluent BOD & TSS below their POTW's surcharge limit. They tried to use their own strategy, but it was ineffective:

- Batch treatment system for 20,000 GPD
- MacDermid Envio Solutions control panel customized for the customer's operations
- A customized chemical regiment to work with the system's design

After closely evaluating the client's facility, operations, requirements and chemistry, **MacDermid Envio Solutions** worked with the manufacturer's in-house experts to create wastewater treatment system tailored specifically to the plant.



Ask about our

DEDEODMA

**GUARANTEE** 

## **RESULTS**

With **MacDermid Envio Solutions** solution, the industrial adhesives and sealant manufacturer's plant:

- Achieved 100% compliant with local POTW wastewater limits
- Eliminated costly surcharges
- Can easily scale for future growth

See our web site for more details www.macdermidenvio.com

**Email:** isenquiries@macdermidenvio.com © 2020 MacDermidEnvio.





